

SMARTBOX: 980241484910
 DATE: 1/19/2010 3:14:26 PM

System ID
 ID: 01,10,00,00,62,40,04,45,47,01
 ,00,58,5a,4a,60,02,00,46

Name: AmerikanCar

SMARTBOX: 980241484910
 DATE: 1/19/2010 3:19:58 PM

| DATA STREAM | VALUE/STATUS |
|-----------------------|--------------|
| MIL Status | OFF |
| FUEL SYS #1 | CL |
| FUEL SYS #2 | UNUSED |
| CALC LOAD | 32.54 % |
| Coolant Temp | 75 °C |
| Short FT #1 | -1.60 % |
| LONG FT #1 | -20.34 % |
| PIM | 33 kpa |
| ENGINE SPD | 933.80 Rpm |
| Vehicle SPD | 0 MPH |
| IGN Advance | 10 Deg |
| Intake Air | -9 °C |
| THROTTLE POS | 10.48 % |
| O2S B1 S1 | 0.52 V |
| O2FT B1 S1 | -3.94 % |
| AT FLUID TEMP | 41.88 °C |
| # Code | 1 |
| Injector | 2.56 ms |
| IAC Duty Ratio | 36.36 % |
| PS Oil Press SW | OFF |
| STOP LIGHT SW | OFF |
| Elect Load SIG | OFF |
| PNP SW | ON |
| A/C SIG | OFF |
| Starter SIG | OFF |
| FC TAU | OFF |
| FC IDL | OFF |
| PS SIGNAL | OFF |
| CHECK MODE | OFF |
| AS Test | COPL |
| OXS2 Test | COPL |
| OXS1 Test | COPL |
| Intake CTL VSV1 | OFF |
| Fuel Pump | ON/H |
| A/C MAG Clutch | OFF |
| EVAP VSV | OFF |
| VVT CTRL B1 | OFF |
| Shift | 1st |
| Overdrive Cut SW1 | OFF |
| Overdrive Cut SW2 | OFF |
| ECT power mode / M SW | OFF |
| Reverse | OFF |
| 2nd | OFF |
| Low | OFF |
| 4th(M)/Drive | OFF |
| 3rd | OFF |

Name: AmerikanCar

SMARTBOX: 980241484910
 DATE: 1/19/2010 3:12:21 PM

- Initialing
- . OBDII SAE J1850
 PWM mode [Failed]
 - . OBDII SAE J1850
 VPW mode [Failed]
 - . OBDII ISO 14230-
 4 KWP QUICK mode [Failed]
 - . OBDII ISO 14230-
 4 KWP ADDRESS mode [Failed]
 - . OBDII ISO 9141-2
 mode [Failed]
 - . OBDII ISO 15765-
 4 CAN mode []

Name: AmerikanCar